

Differential Current Relay KDS



Technical Data

Auxiliary Voltage

24 V DC (18 – 36 V DC)
230 V AC / 12 V DC *

Power Consumption

approx. 4 W at 24 V DC
approx. 6 VA at 230 V AC
*on customers request

Digital Inputs

LowActive
(contact voltage 12 V DC, 5 mA,
opto-decoupled)
cables not longer than 3 m.

Relay Outputs

230 V / 50 Hz / 2 A (potential free)

Measuring Ranges:

Current:

approx. 0.02 to 4.0 A AC (1 A Version)
approx. 0.08 to 20.0 A AC (5 A Version)
tolerance < 0.2 % of full scale

Frequency:

15.0 Hz up to 100.0 Hz
from approx. 150 mA measured
accuracy < 0,01 Hz

Climatic Conditions

acc. to DIN EN 60255-1 (09-2010) ambient
temperature:
in operation: -20 ... +55 °C
transport / storage: -25 ... +55 °C

Housing Dimensions

W / H / D 100 x 75 x 110 mm
for mounting on 35 mm top-hat rail
according to DIN EN 60715

Description	Order number
<p>The KDS 3xx is a device for measurement and monitoring of differential current at generators, motors and transformers. As well possible is the monitoring of mixed constructions, such as a generator with an upstream transformer. In addition to the differential current, it is also possible to measure the individual conductor currents as well as the earth current in three-wire networks. The connection to the system must be done using external current transformers.</p> <p>The KDS 3xx includes the following protective functions [according to ANSI/IEEE C37.2]:</p> <ul style="list-style-type: none"> - Protection on differential current for generators, motors and transformers [87GP, 87MP, 87TP] - (Earth-) overcurrent protection [50, 50N, 50G] - Overcurrent-time-protection [51] - Frequency monitoring [81U, 81O] <p>The comfortable configuration of all settings of the DSR-8 is done by means of the parameterisation software KuPa010 (– Version V2.36 or later required). Alternatively values can be entered directly at the device. Any access to the device's parameterisation can be protected by a PIN. The output of display-texts at the device standardly takes place in German and English (switching between languages is possible at any time during operation). Alternative languages, suitable to the customers' requirements, can be configured and conveniently made available, by means of our parameterisation software Kupa010.</p>	<p>Ordering Information:</p> <p>DSR-8 / 1 A / 24 V DC: 2W301KDS00 DSR-8 / 5 A / 24 V DC: 2W305KDS00</p> <p>Accessories:</p> <p>USB A : USB Mini B parameter. cable 1,5 m: on request parameter. cable 3,0 m:</p> <p>current transformers, various converter ra- tios, e.g. 200A/5</p>